



ISO 9001/2015 nr. IT99/0348 certification  
 ISO 14001/2015 nr. IT18/1174 certification

## TECHNICAL SHEET

### POLYURETHANE

## INK FOR LEATHER® SPRAY TOP 5485 HF

USE        Fixative  
 PHASE    Water

INK FOR LEATHER® SPRAY TOP 5485 HF is a semi-soft and semi-matt fixative that forms a thin film with a waxy touch, designed to guarantee high fastness to rubbing test. Its main application is for articles of leather goods and / or full-grain furniture with natural look, which need to be protected from abrasion caused by daily use and which therefore must pass rubbing resistance tests, performed with Veslic or Crockmeter. It is recommended to use on leathers dyed with our exclusive INK FOR LEATHER range and then sprayed with the products of the INK FOR LEATHER SPRAY system, in order to obtain equalizing finishes with a natural look, but with very high overall fastness. It can be applied alone or with small additions of specific touch modifiers, such as VIP® 5050, and cross-linked with our PROXY® 2080, PROXY® 2060 or PROXY® 2061.

CHARACTERISTIC	EXPECTED VALUE	SPECIFICATION VALUES	UNITS	REFERENCE METHOD
Appearance		White liquid		Visual
Solids	11	10.5 -11.05	%	IS 05-02

VERSION 1 del 03/08/2018

*The information contained in this technical data sheet is based on our best acquired knowledge; However, it must be considered without warranty and does not exempt the customers from performing tests on their own. The application and use of the products are beyond our control and, therefore, the responsibility falls exclusively upon the customer.*